

# TECHNICAL REPORT

## CRIB 5



A - Ziya Gökalp mah.  
Atatürk Bulvarı No:104  
34490 Basakşehir / İstanbul / Türkiye

Customer information: HOEPKE

Höpke Möbelstoff-Handels GmbH •  
Simonsgasse 19 - 21 • 96489  
Niederfüllbach

Our Ref: CR109801-1

Date: 11/10/2022

Delivery Date: 03/10/2022

Test Dates: 06/10/2022

For the attention of :Hilmar Carl

### SAMPLE(S) FOR TEST:



One, Composite - Ref: Marina FR

*Note: The above descriptions are as supplied by the client and have not been verified by K-TEX LAB International who can take no responsibility for the accuracy of the description.*

### TEST REQUIREMENTS:

BS 5852: 2006, Clause 11 Ignition Source 5

### RESULT:

Pass - P 5

The cover material was subjected to the water soak procedure and line dried in accordance with Annex E of the above regulations.

This Report relates to the sample(s) submitted for test and no others. Additions, deletions or alterations are not permitted.

Test reports are given to the client in confidence, and may only be reproduced in whole or in part with written permission from K-TEX LAB International Limited. Note that the words "tested by K-TEX LAB International" may be used in subsequent publicity for the product; "approved" must **not** be used.

Tests are carried out on the understanding that neither K-TEX LAB International Limited nor its officers can accept any legal responsibility for information or advice given or opinions expressed whether in response to specific enquiries or otherwise.



# TECHNICAL REPORT

## CRIB 5



### DESCRIPTION

Enquiry No. CR109801-1

Item: One, Composite Ref: Marina FR

Supplied by: HOEPKE

*The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.*

### IGNITABILITY TEST ACCORDING TO BS 5852: 2006- METHODS OF TEST FOR ASSESSMENT OF THE IGNITABILITY OF UPHOLSTERED SEATING BY SMOULDERING AND FLAMING IGNITION SOURCES

**Initial Inspection:** Condition as new.

**Conditioning:** ≥3 days at indoor ambient conditions and ≥24 hours at 23±2°C & 50±5%rh.

**Test Method:** The test was performed using the specified rig (section 7.2 of the above standard). Using supplied cover and filling components to form a composite that is intended to be representative to the upper 75mm of the upholstered furniture when in final use. The test was conducted using Ignition Source 5.

**Filling Material:** A combustion modified high resilience foam 50kg/m3 Ref: CMHR50.

**Test Conditions:** The test was performed with the stipulated conditions 10°-30°c and 15%-80% relative humidity.

### RESULTS

Source No.	Application No.	Flaming of Assembly	Smoke/ Smoulder	Ignition/ Non-Ignition
5	1	04min 42sec	10min 00sec	PASS (N/I)
	2	04min 58sec	10min 00sec	PASS (N/I)

### COMMENTS

CLAUSE	SMOULDERING FAIL CRITERIA	APP. 1	APP. 2
4.1.1a	Unsafe escalating smouldering	PASS (N/I)	PASS (N/I)
4.1.1c	Smoulders to extremities/ Reaches side of rig/ though full thickness	PASS (N/I)	PASS (N/I)
4.1.1e	Smouldering continued for >60mins from application of ignition source	PASS (N/I)	PASS (N/I)
4.1.1f	Evidence of charring within the filling >100mm horizontally from position of source	PASS (N/I)	PASS (N/I)
CLAUSE	FLAMING FAIL CRITERIA	APP. 1	APP. 2
4.2.1a	Unsafe escalating combustion	PASS (N/I)	PASS (N/I)
4.2.1b	Test specimen consumed during duration of the test	PASS (N/I)	PASS (N/I)
4.2.1c	Flames reach the extremities or penetrate the full thickness of the sample	PASS (N/I)	PASS (N/I)
4.2.1e	Flames >10min from application of ignition source	PASS (N/I)	PASS (N/I)

### CONCLUSION

This sample Ref. Marina FR passes the requirements of BS 5852: 2006 Clause 11, Ignition Source 5.

Tested by: Kadir ÇELEBI

Reported by: Şakir KARATAŞ

Approved by: Aydın KAZAN

